25X1A

25X1A

		Copy 7 of 8
		20 December 1968
MEMORANDUM FO	OR: Deputy for Operat	ions, OSA
SUBJECT:	Detailed Trip Repo	ort. 3 - 10 December 1968
Project and t	Detachment "G" to into initiate Detachment following IW-3 cleare	roduce the

USAF review(s) completed.

	IDEA 0944 Page 2	-68
] 25X1A
fol	lowing subject areas were briefed:	
	a. The NRO requirement.	
m€	b. The concept developed to satisfy that ent. U-2R,	require-
	c. The Quick Application/Evaluation Progr	am,

g. Program costs.

d.

e.

The

25X1

25X1

h. Phase I approved schedules and suspense dates based on a 4 November 1968 go ahead date.

Phase I, and the follow on, refined program, Phase II.

vehicle characteristics.

History of Program development.

The briefing precipitated a lively discussion period thereafter. Discussion chiefly concerned:

a. Impact of this new program on Detachment "G's" training and flight test requirements and current deadlines.

25X1D

25X1A

25X1A

25×1/

PMR Special Projects

procedures for use of the range and its facilities during the flight test and training phases. Other attendees at this

perations

conference were:

25X1A

25X1A

25X1 25X1

25X1A

25X1

	IDEA 0944-68 Page 4	
		25X1A
		•
insure prope facilities.	and were briefed IW-3 prior to these range director and Captain ge operations officer, are also briefed IW-3 to er priority given scheduling and use of range ole areas of discussion were:	25X1A
a.	Range Scheduling:	
	(1) Hours of operation	
	Monday - 1100L - 1930L	
	Tuesday, Wednesday, Thursday - 0500L - 193	30L
	Friday - 0500L - 1500L	
•	(2) Busiest period daily 1000L - 1400L.	
	(NOTE: PMR had conducted 27,020 operations period February 1967 to date.)	
con	(3) schedule should be given on Monday of week preceding the flight. All flicts are resolved and range schedules firmed by Thursday.	

Approved For Release 2003/09/30 : Otto-RE

(4) representative insured that this project will be given top scheduling

priority and only those other projects with the same priority will require consideration in the event of a conflict.

- (5) Schedules will be coordinated via telecon directly between Detachment "G" operations and cleared contacts at the PMR. Conflicts to the desired schedules will be handled in the same manner. If conflicting parties remain intransigent, arbitrates the matter to a decision. No problems are anticipated since Detachment "G" can easily schedule take offs early enough to enter the range before peak load times. Range also will be requested for back up dates in the event unable to complete on primary date. When schedules are firm, Detachment "G" will advise Project Headquarters via priority message.
- (6). PMR scheduling officers, through automation, have a data recall capability which is able to display any selected day's schedule. Data displayed includes:
 - (a) Program identification code number assigned when PMR prepares project operations plan.
 - (b) Aircraft type (if classified, not given).
 - (c) Missile type (if classified, not given).
 - (d) Altitudes of operation.
 - (e) Assigned time block.
 - (f) Range facilities required for project.
- b. Range Facilities:
 - (1) Tracking and surveillance radars are

numerous - able to track all vehicles simultaneously - data link to selectable scales/displays for plotting vehicle track and surveillance scope in control center. Willing to operate as many radars as possible to enhance tracking data collection and System 17B signal environment.

- (2) Optical tracking several high altitude tracking stations available with video capability to closed circuit TV monitor system. TV consoles are available in each of the control centers.
- (3) After each flight PMR will provide: track and altitude plots from tracking radars; surveillance radar scope photography (16mm); automatic gain control (AGC) records from tracking radars to facilitate vehicle radar cross section analysis; 35 or 70mm camera film from Theodolite and MOTU (Mobile Optical Tracking Unit) facilities.
- (4) Air Sea Rescue on alert during all operations primarily helicopters stationed at San Nicolas Island and Pt. Mugu NAS. Sea borne traffic would also be diverted if required.
- (5) Communications all HF, VHF and UHF. PMR assigns discrete UHF frequencies for each operation. Will monitor our assigned HF frequencies. Two way communication available in each control center. Range call sign

- (6) Control Centers real time mission track and altitude plot to monitor mission progress. Equipment includes surveillance radar console TV monitor Air/ground communication. Personnel required in center during mission:
 - (a) Range Operations officer (cleared IW-3).
 - (b) Two uncleared technicians.
 - (c) Detachment "G" operations officer.

IDEA 0944-68 Page 7

This project will be assigned Alfa or Bravo control center.

c. Range Requirements:

- (1) Project Headquarters will detail PMR facilities desired for flights and advise so range operations order can be prepared.
- (2) Two way radio communications with launch aircraft to give/receive acknowledgement of Go/No Go/Hold Fire command. Also desire count down to launch to facilitate immediate acquisition
- (3) Identify safety zone for flight track 25X1 which takes into consideration vehicle capabilities/tolerances in range and azimuth. This zone to be swept clean of aircraft and surface vessels prior to launch go ahead.

d. Clearances:

- (1) FAA File normal flight plan with handoff to PMR prior to entry into range warning areas.
- (2) Range Will clear U-2R onto range upon initial contact and give Go/No Go/Hold Fire command. PMR will coordinate with FAA closure of controlled air way corridors through the range. (One of three must always be available for normal operations. See Attachment 1.) Return U-2R to FAA control upon completion of mission on the range.

e. Security Considerations:

- (1) Radar Tracking technicians will know speed/altitude of all vehicles.
- (2) Optical Tracking operators and all TV monitor stations will observe U-2R configured with and subsequent launch. Can be curtailed.

(3) Schedule - names of project officers - hold down on type aircraft/missile - curtailment of optical tracking - all create curiosity for covert type project.

(4) Communications
Necessary

communications are few and the operations console
appears to be far enough away from the technician's
work area as to preclude overhearing voice
communications. Use of a discrete UHF frequency

should further reduce exposure.

(5) Russian trawlers which are fully equipped for intelligence collection operate within 500NM of Pt. Mugu approximately one third of the time. At random frequency, they anchor inside San Nicolas Island. PMR publishes a daily advisory concerning the location of these ships whenever they are operating within 500NM of Pt. Mugu.

(6) Both are scheduled to be TDY on another operation for two weeks during period 26 January 1969 thru 15 February 1969. Action has been taken to obtain an IW-2 clearance for so that he may function as operations officer during their absence.

- (7) The West Coast security representatives were advised to submit their recommendations concerning these and other security aspects to Project Headquarters for consideration in the development of the overall security/cover plan for this project.
- 3. Recommendations/comments concerning use of PMR are:
- a. Develop a range safety zone which uses the smallest number of control areas and lies inside the Pt. Mugu warning area complex to ease scheduling and

25X1

25X1A

25X1

25X1

IDEA 0944-68 Page 9

range sterilization problems. Should not plan to use since it is controlled by the San Diego range. This action has been accomplished (Attachment 2) with the following considerations: (1) Launch safety zone allows for navigation error up to 5NM each side of planned track as well as along track errors. 25X1 In the event of a single launch, the second can be simulated, etc. San Nicolas tacan may be used as navigation cross check to determine launch point. tacan is available for operational mission. Tacan should be turned off after launch number two before SAM engagement period. (4) The is designed to consider vehicle performance tolerances for a double live launch (#1 flies 10 minute profile, #2 flies 8 minute profile) and reasonable wind and 25X1C navigation errors.

c. With implementation of this security/cover plan, recommend that PMR be allowed to use maximum facilities

in support of this project's operations so that we may obtain the maximum benefit from available data collected by these facilities.

d. PMR desires if possible, since vehicle cross section is small and difficult to track. However, if unit cost prohibitive, recommend no further consideration.

25X1

- e. Detachment "H" and LAC recommends U-2R chase be flown for all launch missions. Hand held camera photography would be taken from offset below launch aircraft which, in their opinion, would facilitate evaluation of launch process, malfunction, etc. Do not recommend approval of these additional flights due to flying safety aspect and the amount of higher priority scheduled committments for time period January February 1969. Q-bay camera installation plus optical tracking by PMR should satisfy these requirements.
- f. Recommend only flights with live vehicle firings be scheduled into PMR. Dummy launches can be accomplished over the Edwards range or the Tonopah range

25X1

- g. Detachment "G" will be tasked to:
- (1) Coordinate Headquarters desires with respect to PMR facilities approved for use.
- (2) Arrange details for PMR prepared report which will evaluate and critique each launch mission.
- (3) Arrange procedures to pick up PMR take (tracking data, film, etc.) after each flight for movement to Headquarters.
- (4) Detail scheduling procedures to include communications plan.

- (5) Obtain coordinates of PMR radar and optical tracking stations for post flight data correlation.
- (6) Coordinate with Los Angeles and Oakland ARTC necessary FAA clearance procedures for enter/exit PMR.
- (7) Process 16, 35 and 70mm black and white film from PMR prior to shipment to Headquarters.
- 4. Friday and Saturday, 6 and 7 December. Discussion and work session with Detachment "G" Commander and Project Officers to develop:
 - a. range safety zone. (Attachment 2)
 - b. Sample training route to PMR.
 - c. Pilot training program.

Discussions included the forthcoming LAC flight test of the configuration and the operational deployment and employment of the system. Received briefings from the flight planning section concerning:

- a. Recommended U-2R data additions to Project Headquarters Manual 50-1055-3, Flight Planning Manual.
- b. An excellent and detailed study prepared by JACKSON flight planner, which analyses the accuracy of U-2R performance charts in the Flight Handbook. Recommend formal recognition be prepared and forwarded through appropriate channels, commending for this outstanding contribution.

5. In developing a recommendation for a pilot training program, certain premises that were established during the formulation of the _______concept were discussed with Detachment "G" project officers. These are:

a. will be used because targeting may change the primary requirement to an overflight mission.

.

25X1

25X1

25X1A

25X1C

- Training to be accomplished at Edwards because:
- Can be accomplished concurrently with systems flight testing.
- Range safety during actual practice launches.
 - (3) Security.
- Better facilities available to further evaluate system performance.
 - (5) Availability of U-2R.

25X1

- The following training program was developed and is considered ideal in view of the ground rules established above but not possible with the present planned inventory of live/inertT vehicles:
 - Ground Training:
 - (1)

25X1

- (2) Operational mission profile.
- (3) Launch/panel procedures.
- (4) Special navigation procedures.
- (5)U-2R requal briefing.
- (6) Training mission planning/briefings.
- b. Flying Training:

- (1) T-33* (one sortie)
 - (a) Local area/range familiarization.
- (b) FAA, departure, enroute, arrival procedures.
 - (c) Recurrency check.
- (2) U-2R* nonconfigured (two sorties)
 - (a) Low altitude day check out.
- (b) High altitude day nav simulate operational route.

*Depends on pilot's currency/qualifications. Possibly time will permit requal at Detachment "H" after U-2R deployed.

- (3) U-2R configured sorties (three sorties)
 - (a) Low High, local area captive.
 - <u>1</u>.

25X1

- $\frac{2}{5}$. 20 40M check flight characteristics, stalls, turns, etc.
- 3. 70M check flight characteristics, buffet, etc.
- 4. Full stop landing with aboard.
- (b) Max altitude over land simulated operational mission.
 - 1. Launch

25X1

25X1

2. Launch point at Edwards or Tonopah range.

	IDEA 0944-68 Page 14	
1aunch	. Assymetrical flight between es.	
<u>4</u>	. Land clean.	• .
(c) M operational	ax altitude over water simulated mission.	
<u>1</u>	. Launch	25X1
<u>2</u>	. Launch 2	25X1
<u>3</u>	. Launch point in PMR.	
<u>4</u>	. Land clean.	
c. Recommendat	ions:	
(1) Each cutlined above.	receives all the training 25	X1A
(2) The IP configured trai		X1A
(3) Assyme in dire emergen	trical configuration for landing only cy. 25X	(1A
d. Sorties req	uired: 25	X1A
	Total	
T-33*	1 0 2	
U-2R* (nonconfig)	2 0 4	

(config)

Total

U-2R

15

^{*} Depends on pilots currency/qualifications.

IDEA	0944-68
Page	15

25X1

f.

- 7. Since Phase I requires an absolutely austere approach the following is the recommended approach to accomplish pilot training with the available inventory:
 - a. Ground training T-33 and nonconfigured U-2R requalification flights no change to that outlined above
 - b. Configured Flight #1

(1)

- (2) Low High Captive
- (3) Check flight characteristics.

(4) Full stop landing with	aboard.	25X1
c. Configured Flight #2 - pilot) only:](primary	25X1A
(1) Max Altitude - simulated operat	ional missio	n.
(2) Launch in Edwa Tonopah range.	rds or	25X1
(3) Navigation and assymetrical fli	ght to PMR.	•
(4) Launch in PMR.		25X1
(5) Land clean.		
d. Configured Flight #2 - pilot) only:	(back up	25X1A
(1) Max Altitude - simulated operat	ional missio	n.
(2) Launch in Edw.	ards or	25X1
(3) Assymetrical flight between lau	nches.	
(4) Land clean. e. Sorties required:		
e. Sorties required:	То	_{ta1} 25X1A
T-33* 1	0	2
U-2R* (nonconfig) 2 2	0	4
U-2R (config) 2 2	1	<u>5</u>
Total 5 5	1	1
* Depends on pilots currency/qualifications.		*

g.

8. The undersigned realizes that there are any number of variations possible between what is the considered ideal training program and the recommended austere approach.

10. Monday, 9 December. Meeting with LAC engineers at the "Skunk Works". In addition to the undersigned, the following personnel were in attendance:

25X1A

25X1

25X1A

Subjects discussed were:

- a. Details of aircraft modification the configuration to be mounted at wing station 161.5 (approximately 10 feet outboard of engine air intake).
- b. Predicted flight characteristics LAC feels assymetrically configured flight will be no problem and will require only negligible amounts of trim change due to the low drag profile of relatively inboard location of the mounts. No adverse yaw/roll is expected at launch and should be controlled with autopilot. LAC predicts that landings and take-offs will be well within the capabilities of the U-2R and should present no unusual problems.
- c. Flight test program LAC anticipates about four flights. will detail LAC requirements and forward to Headquarters as soon as possible. However in the interest of maximum safety precautions recommend a preliminary message to LAC requiring:
 - (1) No landings with the unsymetrical configuration.
 - (2) First inert launch to be accomplished at relatively low altitude (30 40M) to ensure proper separation, etc.
 - (3) Second inert launch at operational altitude.
 - (4) Live launch from operational altitude.

25X1

- d. LAC agreed to develop, at no additional cost, a Flight Handbook supplement concerning the configuration, as well as normal and emergency procedures check lists.
- e. LAC agreed to validate performance data degradation estimates during flight test.
- 11. Monday evening, 9 December. Attended an informal meeting with Beech Aircraft Co. representatives. Attendees in addition to the undersigned were:

Discussions principally concerned:

a. overall reliability - excellent 95% plus.

- b. Autopilot reliability the modified version has an improved autopilot and should hold heading within $\pm 5^{\circ}$ of launch heading.
 - c. Engine very few failures have been experienced.

d. Destruct system - totally reliable and safe.

25X1D

25X1A

- f. Beech will develop checklists for LAC inclusion in Flight Handbook.
- g. Beech agreed to assist in the pilot training program. will be the Beech technical representative at Detachment "G" and he will prepare a slide briefing on for presentation to all

25X1A

25X1

25X1,

25X1A

25X1A

25X1A

IDEA 0944-68 Page 20

interested personnel. In addition, he volunteered to conduct a hangar classroom using the actual equipment as training aids. will provide reference manuals and other materials for study purposes.	25X1/
12. Tuesday, 10 December. Attended D/M/OSA sponsored interface meeting at LAC, Burbank. Details of the meeting should be presented in other trip reports. Items of interest to D/O/OSA that developed at this meeting were:	
a. The	
b. All participants examined the launch panel designed by and were convinced that it would take deliberate action by the pilot It was recommended that the panel be taken to Detachment "G" and its installation in the cockpit determined using a pilot with in inflated pressure suit.	25X1/
c. The proposal requiring the launch and jettison circuits to be interlocked with a landing gear up switch was disapproved. This circuitry feature would not have allowed launch/jettison with the landing gear in the down position which is normally the case from high in the descent profile. Any malfunction occurring after the gear is extended would preclude jettison unless the pilot is able to get the gear back up and locked.	25 Y 1/
10CReu.	25X1 <i>F</i>

Attachments - 2

IDEALIST Division, OSA

IDEA 0944-68 Page 21

25X1A

IDEA/OSA/ (20 Dec 68)

Distribution:

#1 - D/O/OSA

#2 - ASD/R&D/OSA

#3 - MD/M/OSA

#4 - IDEA/OSA

#5 - SAS/OSA

#6 - SS/OSA

#7 - RB/OSA

#8 - Holdback